



# RADIOWORLD

Check [www.RadioWorld.co.uk](http://www.RadioWorld.co.uk) For Latest Prices

**263 Walsall Road, Great Wyrley, Walsall, WS6 6DL**

Established 1997. Open Monday - Friday 9am - 5pm and Saturday 9.30am - 4pm

Tel: **01922 414 796** Fax: **01922 417829** Skype: **radioworld\_uk**

## Hy-Gain T-2XX Tail Twister Rotator £1024.96



## DESCRIPTION

**T2X Tailtwister Series II** for large medium antenna arrays up to 20 square foot wind load  
The T-2XX is the base model for use with 220V power.

The Tail twister is one of the most popular rotators in the Hygain product line. It has been the standard to what competing rotators try to match up to for well over years.

The T2X Tail twister Series II Rotator is for large medium antenna arrays up to 20 square foot wind load. Its wind load with mast adapter is 10 square feet. It has 1000 inches-pounds in turning power and 9000 inches-pounds in brake power. The effective movement in the tower is 3400 feet-pounds.

A new automatic 5-second brake delay insures that the rotator is fully stopped before the brake is engaged. No more accidentally engaging the brake while the rotator is in movement. T2X features a new low temperature grease which permits normal operation to -30° F. New alloy ring gear has tensile strength of 100,000 psi for max reliability.

The indicator potentiometer has been improved for greater reliability. A silver-plated relay contact point makes for smooth traveling and more reliable contact between the pot strip and wiper arm gives years longer life on these important, internal components.

New water-tight AMP detachable twist-and-lock connectors at the rotator base and an 8-pin plug at the control box make it easy to hook up. Rotator has a triple bearing race with 138 ball bearings for large load bearing strength. Electric locking steel wedge brake prevents wind induced antenna movement.

The control box features a North or South center of rotation scale on meter and low voltage control for safe operation.

Clamp plate and stainless steel mounting hardware is included for a up to a 2 1/16 inch mast.