



# RADIOWORLD

Check [www.RadioWorld.co.uk](http://www.RadioWorld.co.uk) For Latest Prices

**263 Walsall Road, Great Wyrley, Walsall, WS6 6DL**

Established 1997. Open Monday - Friday 9am - 5pm and Saturday 9.30am - 4pm

Tel: **01922 414 796** Fax: **01922 417829** Skype: **radioworld\_uk**

## TTI TCB-R2000 MULTI-STANDARD CB RADIO + REMOTE DISPLAY

**£149.95**



### DESCRIPTION

The TCB-R2000 is the new flagship model in the TTI CB range and is probably the most technologically advanced CB radio available on the market today. It is packed full of new and innovative features and is supplied as three main components allowing you flexibility in various mounting options.

The main transceiver comprises of the main unit that is supplied with front mounting speaker, normal fist microphone socket, remote hands-free microphone jack, AUX jack, remote control unit jack, and remote LCD unit jack (please note both of these jacks are also repeated on rear of unit). On the rear there are further jacks for extra remote PTT / foot switch not supplied), external S-meter (not supplied), external speaker jack (not supplied). The main unit can be DIN mounted with the DIN mounting bracket that is supplied, or can be hidden in any other space in the vehicle cabin (under the seat for example).

The remote LCD unit allows you to view the operational functions and control many functions including switch power ON/Off, Manual Squelch level or DSS (Dynamic Squelch Level), Volume & Menu Mode, Channel UP, Channel Down, Scan & Scan Memory, AM/FM (AM not available in UK mode) or Channel 9/19 Selection, Attenuation & Favourite function Programme Button (dealer programmable), Dual Watch & Band Selection Button. The LCD Backlight colour can be selected in any of three colours (Blue, Green, or Orange) and the whole LCD unit can be mounted on sturdy metal bracket with Tilt & Swivel facility.

The Remote Control Unit is a wired "remote" control that allows you to control some key functions of the TCB-R2000 such as PTT and Call function, Menu Mode & AMG (Automatic



- **Multi-Standard**
- **Graphic Channel & Volume Display**
- **ID Writing**
- **Menu Mode (with extra functions like Roger Beep, Squelch tail Reduction, etc)**
- **Programmable Function Key**
- **Scan & Scan Memory**

D Germany 80CH FM 4 watts / 12CH AM 1 watt  
 D2 Germany 40CH FM 4 watts / 12CH AM 1 watt  
 EU Europe 40CH FM 4 watts / 40CH AM 1 watt

- **Frequency Read Out**
- **Comander Noise Reduction Circuitry**
- **38 CTCSS Sub-channels**
- **Attenuation**
- **Remote PTT Capability**

Frequency 26.965Mhz to 27.405Mhz (CEPT)  
 27.60125Mhz to 27.99125Mhz (UK)

- **VOX**
- **Speaker Mute**
- **External Speaker Jack**

Power Supply 13.8V DC / 24V DC

- **External S-meter Jack**
- **AMG**
- **Squelch Control & DSS**

Sensitivity 0.7µV for 20dB SINAD in FM mode / 0.7 V for 10dB (S+N)N in AM mode

- **3 Colour Backlight selection**

Size 190mm (w) x 58mm (h) x 656mm (d)

**Technical Specifications:**

Frequency Bands EC CEPT 40CH FM 4 watts

E Spain 40CH AM/FM 4watts

F France 40CH FM 4 watts / 40CH AM 1 watt

PL Poland 40CH AM/FM 4 watts (+ / - 5KHz)

UK UK 40CH FM 4watts

UE UK 40CH FM 4 watts / 40CH CEPT (EC) 4 watts

I Italy 40CH AM/FM 4 watts

2 Italy 34CH AM/FM 4 watts